



Proluxe Low Profile 630 Diesel Jet



Proluxe 630 with low profile tilting console resulting in 4.6' (1.40m) overall height

This beautiful yacht tender was especially built to fit the demanding requirements of the owner and with the constant help of the Yacht Captain and the Yacht designer. The low profile enables two of these tenders to be stored in the designated yacht garage and the custom passenger boarding steps at the stern allow the owner and his party to board and disembark directly into the beach. This model is also available as a Rescue Boat suitable for acceptance to the MCA code.

630 DJ GENERAL SPECIFICATIONS

Length overall	22.00'	Sponson material	1670 neo/hypalon
(does not include outboard)	6.70 m	Max. Horsepower	315
Beam max.	8.5'	Min. horsepower to plane	150
(inflated)	2.59 m	Fuel capacity – main	48 US gal.
Draft	17" or 0.43 m		181 liters
Length rigid hull	19.0'	Person capacity	15A + OC
(from transom top to bow)	5.79 m	Weight capacity	2913 lb.
Tube diameter	21 in	(including fuel)	1324 kg
	0.53 m	Payload	2249 lb.
Number of chambers	5	(excluding fuel)	1022 kg
Tube volume	101 cu.ft.	Approx. hoisting weight	4050 lb.
	2869 liters	(max. weight w/ no crew)	1840 kg
Hull material	Aluminum		





Proluxe 630 Low Profile DJ Complete Description

DESIGN DETAILS

- GRP Military "V" Lift: 4 lift points (Fwd 2 recessed in deck)
- GRP engine cover with power lift that forms a seating leaning bolster cushioned for driver and passenger fwd and 2 passengers facing aft, seat hand rails
- Console hatch door
- Aft bench seating (walk thru access to swim platform)
- Transom swim platform
- Console handrail, windshield

GRP HULL / DECK

- Hull with self-draining non-skid deck
- Hull drain plug
- 2 transom scuppers
- Reinforced bow towing eye, 2 SS towing/tie-down eyes on transom
- ISO 6185 Floatation Foam

COLLAR

- Inflatable collar with 5 chambers
- Intercommunicating filling/overpressure relief valves (4)
- Double rubbing strake
- 2 recessed cleats in step treads, 2 step treads, anchor roller with cleat

ELECTRICAL

- Under-deck cable routing with "wire fishing" line
- GRP console: tilting for low profile
- Electrical panel with 20 circuits, battery(s) storage, battery switch, accessory plug (12v)
- Navigation lights with telescoping stern light, courtesy lights on deck
- Auto bilge pump, electric horn
- Battery condition indicator, dimmer switch

PROPULSION SYSTEM

- Under-deck 48 US gallon tank
- Bow fuel fill with cushion
- Fuel gauge
- Hydraulic steering and tilt helm
- Racor fuel water separator
- Hamilton 213 waterjet
- Volvo 42WJ 230 HP

MISCELLANEOUS DATA

- 4 beverage holders; 2 paddles
- Inflation pump, owners manual, collar repair kit

SHIPPING PREPARATION

For information on all available options please contact your Zodiac dealer or visit our website at www.zodiac.com

Disclaimer: Photos may vary with options
Descriptions/Specifications are subject to change
March 2004

The overall appearance of the Proluxe 630 including all available Zodiac options is a protected trademark of Zodiac

ZODIAC HURRICANE TECHNOLOGIES, INC.

7830 Vantage Way, Delta, British Columbia, Canada V4G 1A7

Tel: 604 940 2999 – Fax: 604 940 2779

www.zodiac.com